

Model 600NW+ -GSVO

Gravity/Servo Feed High Speed Net Weigh Scale

Effective Date: January 1, 2018



<u>Effective List Prices (\$ USD):</u>	<u>Simplex</u>	<u>Duplex</u>
Mild Steel	\$31,645	\$58,795
304 SS Contact Points	\$35,770	\$64,200
304 Stainless Steel	\$40,395	\$72,750
316 SS Contact Points	Call Factory for Pricing	

All Net Weigh Scales require a Collating Chute **and Bag Spout for manual applications. See options pages.*

The Hamer Model 600 NW-GSVO is a heavy duty net weigh scale with gravity gate feeders. Scale and feeder housing are constructed of carbon steel. The main scale assembly is built from 2x2 tubular carbon steel. Direct mount load cell weighing increases accuracy and speed, digital readout operator station using Rice Lake 920i digital weight indicator. Optional weigh hopper constructed of heavy gauge, 304 Stainless Steel with air operated double doors of re-enforced Stainless Steel. On the all Stainless steel version, contact points, gravity gate, weigh bucket, and weigh bucket doors are made of 304 Stainless Steel for corrosion resistance.

Standard Features Include:

- Up to 30 BPM (material flow dependent)
- Up to +/- .5 oz. accuracy @ 2 Sigma, product dependent
- Weight range: approximately 10lb to 110lb (5kg to 50kg)
- Dual load cell design maximizes signal strength, and stabilization for increased accuracy and weightment speed
- Rugged weigh hopper doors increase operational life
- 4" dust collection port (1 per scale, 2 total)
- Steep weigh hopper doors ensure fast product discharge, no residue
- Fully enclosed casing with easily detachable side panels for easy access
- Programmable scale control displays scale weights, target tolerances, surge bin fill status
- Controller stores up to 100 pre-set formulas
- NEMA 4X 304SS controller enclosure
- RS-232/485 communications output to printers and other devices
- Controller is UL, CUL, OIML and NTEP approved
- Ethernet Option

Equipment Specifications:

- Dimensions – width 42.88"; height 43.72"; depth 28.00" (Simplex), 56.75" (Duplex); uncrated weight 900 lbs. (Simplex), 1800 lbs. (Duplex)
- Electrical requirement 110VAC, 1PH, 60Hz, 5amp; (230V for servo)
- Pneumatic requirement 80 PSI, 10 CFM